



VG-888S Series 高速細筒型三針五線綑縫機

HIGH SPEED SMALL CYLINDER-BED 3-NEEDLE 5-THREAD INTERLOCK MACHINE

<http://www.shingling.com.tw>

SHING LING
星菱牌工業用縫紉機
INDUSTRIAL SEWING MACHINE




牛角式導布器及活動式壓腳舌，使押袴克骨綑縫更快速、美觀。

Equipped with fabric guide and presser foot front guide make cover stitch convenient and perfect.



“密封式側蓋設計”無任何漏油問題，而特殊短距橫筒設計，從側蓋到壓腳邊緣僅33mm，使綑縫作業更加順暢。

Thanks to "Fully Sealed Side Cover" it assures free from oil leakage. Moreover, shorten distance from side cover to presser foot by 33mm enable to meet sewing work at ease and will.



精巧迷你型細筒圓周179mm的設計，可任意車縫小口徑的細筒型針織布，流暢美觀。

The compact-size cylinder bed minimized the circumference at 179mm can sew any small-size tubular knitwear more conveniently.



專利設計微調式差動調整，可精密調整差動進給量。

Patent design the differential feed ratio level makes the ratio adjustment stable and precise.



圓形細細針縫目調整鈕，可在高速車縫進行中，隨心所欲精確地調整縫目長短。

Round-shape regular can precisely adjust the stitching length when machine is being operated.



智慧型線圈調整裝置，使線圈可隨心所欲調整大小，符合多樣化不了車縫，品質完美之要求。

Smart loop adjuster makes size of needle loop at will.

Function	Spec.	UY128GAS								
併縫 Attaching		3 3 4 4	5 5 6 6	5.6 6.4 5.2 6.0 6.4	1.4-3.6			6	4500	31
折下襠 Hemming		2 2 3 3	4 4 5 5	4.0 4.8 5.6 6.4	1.4-3.6			6	4500	31
喇叭滾邊 Tape Binding		2 2 3 3	4 4 5 5	4.0 4.8 5.6 6.4	1.4-3.6			6	4500	31
壓骨 Stitch Covering		2 2 3 3	4 4 5 5	4.0 4.8 5.6 6.4	1.4-3.6			6	4500	31

Options 可選配	Function 功能
RP	Rear Puller (Gear Type) 後拉輪 (齒輪)
RPA	Rear Puller (Rubber Type) 後拉輪 (平輪)

型號 MODEL	下刀裝置 Under trimmer	上刀裝置 Top trimmer	撥線裝置 Wiper	備註 Power
VG-888S/AST	•	•	•	氣動 Air
VG-888S/AWT	•	•	•	氣動 Air
VG-888S/EST	•	•	•	電動 Electric
VG-888S/EWT	•	•	•	電動 Electric